

TS 320

universal transport system

Convenience and flexibility from A to B. Paper sheets, stacks of paper, brochures, mailers, cardboard etc. often need to be moved short distances and automatically loaded or unloaded. Small differences in height need to be bridged. The BA 320 transport system meets these requirements reliably and efficiently, and offers universal applications.

Outstanding features make this possible: stepless speed control, continuous or scale height-adjustable table-top or free-standing, various applications (feed, transport, delivery), various standard modules (clamp, side guide, collector, etc.). In addition, as a result of its modular design, special customer requirements can be implemented cost effectively.

- universal transport system for feed, transport, delivery
- one piece highly adherent conveyor belt
- continuous or scale
- table or stand version
- various standard modules (clamp, side guide, collector, etc.)
- cost effective customization possible
- robust construction, designed for long-run



TS 320

Features and Technical Equipment



TS 320

Feeding width	320 mm
Transport length	830 mm (standard) other length available on request
Transport medium	one piece highly adherent conveyor belt
Speed	stepless speed control, max. 34 U/min (standard), other speeds available on request
Transport mode	continuous, scale (electronic unit identification)
Stand version	height adjustable table stand, height adjustable stand*
Standard modules*	Hold-down rollers, hold-down bars, collecting plate, collector, side guides 45°/90° left/right, inlet plate, etc.
Customer solutions	on request
Machine dimension	1030 / 420 / 300 mm (table version)
Weight	19 kg
Power supply	240V / 50Hz

*optional

Product images show TS 320 with standard modules: hold-down rollers, side guides 45° right, collecting plate